



230 volt

standard duty **230 volt**
 rotary phase converter

model	largest hp	combined hp	volts	amps	a dim.	b dim.	c dim.	d dim.	e dim.	f.dim	weight
rpc 3/4-2	3/4	2	230	1.8	12"	10"	12"	-	-	-	67lbs
rpc 2-6	2	6	230	1.8	14"	13"	14"	-	-	-	102lbs
rpc 3-9	3	9	230	2.8	16"	14"	16"	-	-	-	125lbs
rpc 5-15	5	15	230	2.5	17"	15"	17"	-	-	-	175lbs
rpc 7.5-20		20	230	8.0	17"	15"	17"	-	-	-	205lbs
rpc 10-30	10	30	230	10.0	20"	20"	21"	-	-	-	282lbs
rpc 15-45	15	45	230	14.0	22"	21"	23"	-	-	-	400lbs
rpc 20-60	20	60	230	18.0	22"	21"	25"	-	-	-	435lbs
rpc 25-75	25	72	230	33.0	23"	26"	27"	-	-	-	575lbs
rpc 30-80*	30	80	230	28.0	21"	16"	27"	32"	24"	10"	770lbs
rpc 40-100*	40	100	230	46.0	25"	18"	28"	36"	30"	12"	1100lbs
rpc 50-120*	50	120	230	50.0	25"	21"	30"	36"	30"	12"	1300lbs

*rotary unit and capacitor enclosure shipped separated and must be connected at installation

dimension drawings

