



460 volt  
 standard duty **460 volt**  
 rotary phase converter

| model              | largest hp | combined hp | volts | amps | a dim. | b dim. | c dim. | d dim. | e dim. | f.dim | weight  |
|--------------------|------------|-------------|-------|------|--------|--------|--------|--------|--------|-------|---------|
| <b>hvc 2-6</b>     | 2          | 6           | 460   | 1.0  | 14"    | 13"    | 14"    | -      | -      | -     | 102lbs  |
| <b>hvc 3-9</b>     | 3          | 9           | 460   | 1.5  | 16"    | 14"    | 16"    | -      | -      | -     | 125lbs  |
| <b>hvc 5-15</b>    | 5          | 15          | 460   | 1.8  | 17"    | 15"    | 17"    | -      | -      | -     | 175lbs  |
| <b>hvc 7.5-20</b>  |            | 20          | 460   | 4.0  | 17"    | 15"    | 17"    | -      | -      | -     | 205lbs  |
| <b>hvc 10-30</b>   | 10         | 30          | 460   | 6.0  | 20"    | 20"    | 21"    | -      | -      | -     | 282lbs  |
| <b>hvc 15-45</b>   | 15         | 45          | 460   | 9.0  | 22"    | 21"    | 23"    | -      | -      | -     | 400lbs  |
| <b>hvc 20-60</b>   | 20         | 60          | 460   | 10.0 | 22"    | 21"    | 25"    | -      | -      | -     | 435lbs  |
| <b>hvc 25-75</b>   | 25         | 72          | 460   | 20.0 | 23"    | 26"    | 27"    | -      | -      | -     | 575lbs  |
| <b>hvc 30-80*</b>  | 30         | 80          | 460   | 18.0 | 21"    | 16"    | 27"    | 32"    | 24"    | 10"   | 770lbs  |
| <b>hvc 40-100*</b> | 40         | 100         | 460   | 22.0 | 25"    | 18"    | 28"    | 36"    | 30"    | 12"   | 1100lbs |
| <b>hvc 50-120*</b> | 50         | 120         | 460   | 24.0 | 25"    | 21"    | 30"    | 36"    | 30"    | 12"   | 1300lbs |

\*rotary unit and capacitor enclosure shipped separated and must be connected at installation

dimension drawings

